



Screws are not visible.. It provides high heat and water insulation. It is suitable for vertical and horizontal installation. Surface options; micro wave and standard. EPS insulated panels are preferred because they are light and environment-friendly, do not produce bacteria (anti-bacterial) and economic.

Dıştan Vida Teknik Özellikler / Outer Screw Technical Specifications

Yalıtım Kalınlıkları Insulation Thicknesses	Yalıtım Yoğunluğu Insulation Density	Metal Kalınlıkları Metal Thicknesses Boyalı Galvaniz Sac ^{PPGI} Dış Yüzey / Exterior Sheet 0,50-0,60-0,70 mm İç Yüzey / Interior Sheet 0,40-0,50-0,60-0,70 mm	Isı İletkenlik Katsayısı Thermal Conductivity Coefficient	Yangın Sınıfı Fire Resistance Class
40-50-60-70-75-80-100 mm	13-20 kg/m ³ (Özel Üretim 13-20 kg/m ³)		$\lambda = 0,038$ W/mK	E (Alev Sürdürmez)
				DÜZ
				MESA
				GROOVE
				GROOVE
				DÜZ
				MESA

Insulation Thicknesses:40-50-60-70-75-80-100mm

Insulation Density: 26-30 kg/m³

Metal Thicknesses/Inner Surface/BGS 0.40-0.50-0.60-0.70mm

Metal Thicknesses/Outer Surface/BGS 0.40-0.50-0.60-0.70mm

Thermal Conductivity Coefficient $\lambda = 0.038$ W/mK